

## Tulajdonságok

**TÍPUS:** 4 UTAS**HŰTŐKÖZEG:** R32/R410a**TECHNIKAI ADATOK:** KÉSZLET**CSATLAKOZÁS:** 1/4" CSATLAKOZÓKKAL**ELZÁRÓ GOMB:** GOLYÓSCSAPOS**GYÁRTÓ:** MASTERCOOL**KÉSZLETEN:** NINCS KÉSZLETEN

## Leírás

Mastercool 4 utas csapterlep. Hűtőközeg: R410, R32 Mértékegység: °C, Bar Mérőóra mérete: 80 mm Elzáró csapos 90cm-es tömlők: Piros / kék: 1/4" x 5/16? Sárga: 1/4" x 1/4? Fekete (vákuum) : 5/16? x 5/16? A blokkon áthaladó 3/8 hüvelykes furat jelentősen növeli az áramlást, a gyorsabb töltést és lefejtést lehetővé téve. A golyóscsap 90°-kal elfordul két teflon alátét között, így kis erőfeszítést igényel még nyomás alatt is. Gyorsan nyílik és záródik, mindössze negyed fordulattal. A gomb helyzete megmutatja, hogy a szelepek nyitva vagy zárva vannak (függőleges = nyitott, vízszintes = zárva) R410, R32 (gauge p/n EBAL1-EBAH1, Class 1.0) manifold gauge set with 3 – 150 cm nylon barrier hoses with manual ball valves at the end (red/blue 1/4 x 5/16?, yellow 1/4 x 1/4? and one 3/8? SAE black vacuum hose All Mastercool gauges are color coordinated for easy refrigerant recognition. 8? bore through the block increases flow considerably, faster charging and recovery Ball valve rotates 90? between two teflon washers requiring little effort to turn, even under pressure Opens and closes quickly with only a quarter turn Knob position shows whether valves are open or closed (Vertical = Open, Horizontal = Closed) 80 mm gauges / 1.6 gauge class